

LED LAMP

VIVID Series



LED A-Shape Bulbs

VIV-A15, A19, A21, PS25, PS30



15,000hrs: 2-year; 25,000hrs: 3-year limited warranty
50,000hrs: 5-year limited warranty

Operating temperature range -40 °C ~ +40 °C
A15 (-20 °C ~ +40 °C)



Features & Benefits

cULus listed, Energy Star / DLC listed*

High CRI (80+)*, dimmable*


25,000 hrs average life*

Enclosed fixture application

Damp location approved

*For applicable models, see product specification below

Dimensional Drawing



Ordering Information Example: VIV-A15/5.5W/27/D/F

Family Name	Lamp Type	Wattage	CCT	Dimmable	Others
VIV (Vivid)	A15	5.5W	27 (2700K)	D (Dimmable)	F (Frost)
	A19	6W, 9W, 11W, 15W	30 (3000K)	Blank (Non-dimmable)	E26 (E26 base)
	A21	18W, 23W, 3way	40 (4000K)		EX39 (EX39 base)
	PS25	27W	50 (5000K)		
	PS30 (DLC approved)	36W			

Product Specification

Ordering Code	Energy Star / DLC	Model Number	Wattage (W)	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture Application	Damp Location	Dimmable	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
High Lumen VIVID 25000hrs/50000hrs, ES/DLC, -40°C~+40°C																
1754406	Yes	VIV-PS25/27W/40/E26	27	E26	120-277	25,000	230°	3200	4000	80	Y	Y	N	3.23	6.73	40
1755404	Yes DLC	VIV-PS30/36W/40/EX39	36	EX39	120-277	50,000	230°	5000	4000	80	Y	Y	N	3.74	7.28	40
1764210	Yes	VIV-A21/23W/30/D	23	E26	120	15,000	230°	2550	3000	80	Y	Y	Y	2.63	4.8	40
1753200	Yes	VIV-A21/90/18W/30/D (CRI 90)	18	E26	120	25,000	230°	2000	3000	90	Y	Y	Y	2.63	4.8	40
1763232	Yes	VIV-A21/3WAY/15W/27/D	15/10/5	E26	120	15,000	230°	1600/1100/600	2700	80	Y	Y	Y	2.63	4.8	40

LED A-Shape Bulbs

VIV-A15, A19, A21, PS25, PS30

Ordering Code	Energy Star / DLC	Model Number	Wattage (W)	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture Application	Damp Location	Dimmable	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
A15 VIVID 25000hrs ES																
1752105	Yes	VIV-A15/5.5W/27/D/F	5.5	E26	120	25,000	220°	450	2700	80	Y	Y	Y	-	3.3	100
1752219	Yes	VIV-A15/5.5W/30/D/F	5.5	E26	120	25,000	220°	450	3000	80	Y	Y	Y	-	3.3	100
1752420	Yes	VIV-A15/5.5W/40/D/F	5.5	E26	120	25,000	220°	450	4000	80	Y	Y	Y	-	3.3	100
A19 VIVID X18 Dimmable 25000hrs, ES, Enclosed Fixtures, -40°C~+40°C																
1762021		VIV-A19/X18/15W/27/D	15	E26	120	25,000	220°	1600	2700	80	Y	Y	Y	-	4.9	40
1762797		VIV-A19/X18/15W/30/D	15	E26	120	25,000	220°	1600	3000	80	Y	Y	Y	-	4.9	40
1762879		VIV-A19/X18/15W/40/D	15	E26	120	25,000	220°	1600	4000	80	Y	Y	Y	-	4.9	40
1762549		VIV-A19/X18/15W/50/D	15	E26	120	25,000	220°	1600	5000	80	Y	Y	Y	-	4.9	40
1762798		VIV-A19/X18/11W/30/D	11	E26	120	25,000	220°	1100	3000	80	Y	Y	Y	-	4.4	40
1762880		VIV-A19/X18/11W/40/D	11	E26	120	25,000	220°	1100	4000	80	Y	Y	Y	-	4.4	40
1762019		VIV-A19/X18/9W/27/D	9	E26	120	25,000	220°	800	2700	80	Y	Y	Y	-	4.4	40
1762799		VIV-A19/X18/9W/30/D	9	E26	120	25,000	220°	800	3000	80	Y	Y	Y	-	4.4	40
1762881		VIV-A19/X18/9W/40/D	9	E26	120	25,000	220°	800	4000	80	Y	Y	Y	-	4.4	40
1762550		VIV-A19/X18/9W/50/D	9	E26	120	25,000	220°	800	5000	80	Y	Y	Y	-	4.4	40
1762020		VIV-A19/X18/6W/27/D	6	E26	120	25,000	220°	480	2700	80	Y	Y	Y	-	4.2	40
1762700		VIV-A19/X18/6W/30/D	6	E26	120	25,000	220°	480	3000	80	Y	Y	Y	-	4.2	40
1762882		VIV-A19/X18/6W/40/D	6	E26	120	25,000	220°	480	4000	80	Y	Y	Y	-	4.2	40