

LED LAMP

ARTISAN Series



LED A15, A19, B10

Low Flicker LOW non visible FLICKER



2-year limited warranty

Operating temperature range -20 °C ~ +40 °C



Features & Benefits


- Reduced flicker down to 10%
 - Compare to 6.6% traditional incandescent
 - Far below California T20 standard 30%
 - Significantly improve light quality
 - Optimize eye comfort

With clear, amber or milky white glass cover

15,000 hour life (L70), high CRI (80+), dimmable

Damp location rated

Dimensional Drawing



Ordering Information Example: AR-A15LF/5W/30/D/C

| Family Name | Lamp Type | Wattage | CCT | Dimmable | Cover |
|--------------|--------------------------|---------|------------|--------------|------------------|
| AR (Artisan) | A15LF (A15, Low flicker) | 4W | 22 (2200K) | D (Dimmable) | C (Clear) |
| | A19LF (A19, Low flicker) | 5W | 27 (2700K) | | A (Amber) |
| | B10LF (B10, Low flicker) | 8W | 30 (3000K) | | MW (Milky white) |
| | BA10 | | 40 (4000K) | | |

Product Specification

| Ordering Code | Model Number | Product Description | Watts (W) | Replacement Filament | Replacement Incandescent | Base | Voltage (V) | Hour Rating | Beam Angle | Initial Lumens (lm) | CCT(K) | CRI | Damp LOC. | M.O.L. (inch) | Case QTY. |
|---------------|-------------------------|---|-----------|----------------------|--------------------------|------|-------------|-------------|------------|---------------------|--------|-----|-----------|---------------|-----------|
| 1771209 | AR-A15LF/5W/30/D/C | A15 Low Flicker 5W 30K Dimmable Clear | 5 | - | 40W | E26 | 120 | 15,000 | 330° | 500 | 3000 | 80 | Y | 3.54 | 40 |
| 1771213 | AR-A15LF/5W/30/D/MW | A15 Low Flicker 5W 30K Dimmable Milky white | 5 | - | 40W | E26 | 120 | 15,000 | 330° | 450 | 3000 | 80 | Y | 3.54 | 40 |
| 1771210 | AR-A15LF/5W/30/D/F | A15 Low Flicker 5W 30K Dimmable Milky white | 5 | - | 40W | E26 | 120 | 15,000 | 330° | 450 | 3000 | 80 | Y | 3.54 | 40 |
| 1772110 | AR-A19LF/8W/27/D/C | A19 Low Flicker 8W 27K Dimmable Clear | 8 | - | 60W | E26 | 120 | 15,000 | 330° | 800 | 2700 | 80 | Y | 4.29 | 40 |
| 1772202 | AR-A19LF/8W/30/D/C | A19 Low Flicker 8W 30K Dimmable Clear | 8 | - | 60W | E26 | 120 | 15,000 | 330° | 800 | 3000 | 80 | Y | 4.29 | 40 |
| 1772205 | AR-A19LF/8W/30/D/MW | A19 Low Flicker 8W 30K Dimmable Milky white | 8 | - | 60W | E26 | 120 | 15,000 | 330° | 750 | 3000 | 80 | Y | 4.29 | 40 |
| 1771141 | AR-B10LF/4W/27/E12/D/C | B10 Low Flicker 4W 27K E12 Dimmable Clear | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 350 | 2700 | 80 | Y | 3.78 | 50 |
| 1771203 | AR-B10LF/4W/30/E12/D/C | B10 Low Flicker 4W 30K E12 Dimmable Clear | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 350 | 3000 | 80 | Y | 3.78 | 50 |
| 1771211 | AR-B10LF/4W/30/E12/D/MW | B10 Low Flicker 4W 30K E12 Dimmable Milky white | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 300 | 3000 | 80 | Y | 3.78 | 50 |
| 1771403 | AR-B10LF/4W/40/E12/D/C | B10 Low Flicker 4W 40K E12 Dimmable Clear | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 350 | 4000 | 80 | Y | 3.78 | 50 |
| 1771925 | AR-B10LF/4W/22/E12/D/A | B10 Low Flicker 4W 22K E12 Dimmable Amber | 4 | 40W | - | E12 | 120 | 15,000 | 330° | 350 | 2200 | 80 | Y | 3.78 | 50 |
| 1771142 | AR-B10LF/4W/27/D/C | B10 Low Flicker 4W 27K E26 Dimmable Clear | 4 | - | 40W | E26 | 120 | 15,000 | 330° | 350 | 2700 | 80 | Y | 3.78 | 50 |
| 1771137 | AR-BA10/4W/27/E12/D/C** | BA10 4W 27K E12 Dimmable Clear | 4 | - | 40W | E12 | 120 | 15,000 | 330° | 350 | 2700 | 80 | Y | 3.78 | 50 |

** AR-BA10 is not the low flicker item