

LED LAMP

HD Series



LED PAR38, PAR30 HD-PAR38, HD-PAR30LN, HD-PAR30



5-year (ES approved), 3-year (non ES) limited warranty

Operating temperature range -20 °C ~ +45 °C




Features & Benefits

- Outstanding high lumen output, for premium and high ceiling applications
- May be used to replace high lumen PAR, including Ceramic Metal Halide (CMH)
- 4 different beam angles to meet your lighting needs
- Dark silver colour housing
- Excellent performance for task lighting
- 50,000 hours average life, Energy Star listed*
- Enclosed fixture application and wet location approved*
- High CRI (Up to 90+)*

*For applicable models, see product specification below.

Dimensional Drawing



	D	L
PAR38	4.8"	5.04"
PAR30LN	3.74"	4.65"
PAR30	3.74"	3.58"

Ordering Information Example: HD-PAR30LN/33W/40/WFL60/D

Family Name	Lamp Type	Wattage	CCT	Beam Angle	Dimmable
HD (HD series)	PAR38	11W	30 (3000K)	SP15 (15°)	D (Dimmable)
	PAR30LN (Long neck)	26W	40 (4000K)	FL25 (25°)	Blank (Non dimmable)
	PAR30 (Short neck)	33W		WFL40 (40°)	
		38W		WFL60 (60°)	

Product Specification

Ordering Code	Energy Star	Model Number	Watts	Replacement CMH	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	C.B.C.P. (cd)	Enclosed Fixture AP.	Wet LOC.	Damp LOC.	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1785203	Y	HD-PAR38/38W/30/FL25	38	100W	E26	120	50,000	25°	4000	3000	80	17500	-	Y	Y	4.8	5.04	10
1785401	Y	HD-PAR38/38W/40/FL25	38	100W	E26	120	50,000	25°	4000	4000	80	17500	-	Y	Y	4.8	5.04	10
1785200	Y	HD-PAR38/38W/30/WFL40	38	100W	E26	120	50,000	40°	4000	3000	80	8000	-	Y	Y	4.8	5.04	10
1785400	Y	HD-PAR38/38W/40/WFL40	38	100W	E26	120	50,000	40°	4000	4000	80	8000	-	Y	Y	4.8	5.04	8
1784201	Y	HD-PAR38/26W/30/SP15/D	26	70W	E26	120	50,000	15°	2400	3000	90	20000	Y	Y	Y	4.8	5.04	8
1784202	Y	HD-PAR38/26W/30/FL25/D	26	70W	E26	120	50,000	25°	2400	3000	90	11000	Y	Y	Y	4.8	5.04	8
1784203	Y	HD-PAR38/26W/30/WFL40/D	26	70W	E26	120	50,000	40°	2400	3000	90	4000	Y	Y	Y	4.8	5.04	8
1784405	Y	HD-PAR38/26W/40/SP15/D	26	70W	E26	120	50,000	15°	2400	4000	90	20000	Y	Y	Y	4.8	5.04	8
1784406	Y	HD-PAR38/26W/40/FL25/D	26	70W	E26	120	50,000	25°	2400	4000	90	11000	Y	Y	Y	4.8	5.04	8
1784407	Y	HD-PAR38/26W/40/WFL40/D	26	70W	E26	120	50,000	40°	2400	4000	90	4000	Y	Y	Y	4.8	5.04	8
1785201	Y	HD-PAR30LN/33W/30/FL25/D	33	70W	E26	120	50,000	25°	3000	3000	90	13000	-	-	Y	3.74	4.65	12
1785402	Y	HD-PAR30LN/33W/40/FL25/D	33	70W	E26	120	50,000	25°	3000	4000	90	13000	-	-	Y	3.74	4.65	12
1785202	Y	HD-PAR30LN/33W/30/WFL40/D	33	70W	E26	120	50,000	40°	3000	3000	90	6500	-	-	Y	3.74	4.65	12
1785403	Y	HD-PAR30LN/33W/40/WFL40/D	33	70W	E26	120	50,000	40°	3000	4000	90	6500	-	-	Y	3.74	4.65	12
1785404	-	HD-PAR30LN/33W/40/WFL60/D	33	70W	E26	120	50,000	60°	3000	4000	90	-	-	-	Y	3.74	4.65	12
1782225	-	HD-PAR30/11W/30/FL25/D	11	39W	E26	120	40,000	25°	1100	3000	80	2910	Y	-	Y	3.74	3.58	30
1782226	-	HD-PAR30/11W/30/WFL40/D	11	39W	E26	120	40,000	40°	1100	3000	80	1315	Y	-	Y	3.74	3.58	30