

LED FIXTURE

SSL Series



LED Compact Parking Garage Canopy SSL-CPG

120-347V auto-sensing driver, 1-10V dimming
Multiple kelvin (CCT) selection



5-year limited warranty


Operating temperature range -40° C ~ +50° C



Features & Benefits

- cULus listed, DLC Premium
- 120-347V auto-sensing, system light efficacy ≥ 135 lm / W
- Switchable CCT (30K/40K/50K), white finish
- Suitable for J-BOX mounting, and pendant mounting
- 150° beam spread, PC lens
- Installed sensor socket allows for ease of sensor installation, sensor sold separately
- L70 @ 50,000 Hrs, CRI \geq 80
- IP 65, wet location rated

Dimensional Drawing



	DIA/ D H	
25W, 40W, 60W	10"	3.1"
75W, 100W	11"	3.1"

Ordering Information Example: SSL-CPG/25W/MK/120-347V/WH/D

Family Name	Fixture Type	Wattage	CCT (Kelvin)	Voltage	Finish	Dimmable	Options
SSL (Solid state lighting)	CPG (LED compact parking garage canopy)	25W, 40W, 60W 75W, 100W	MK (Multi Kelvin/ CCT)	120-347V	WH (White)	D (Dimmable)	SSL-CPG/LV/12V/SENSOR SSL-CPG/LV/12V/CONTROLLER

Product Specification

Ordering Code	DLC Premium	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Wet Location	Dimension D×H(inch)	Case QTY.
3664309	Y	SSL-CPG/25W/MK/120-347V/WH/D	25	120-347V	50,000	3110	30-40-50	≥ 80	Yes	10 x 3.1	1
3665314	Y	SSL-CPG/40W/MK/120-347V/WH/D	40	120-347V	50,000	5130	30-40-50	≥ 80	Yes	10 x 3.1	1
3666315	Y	SSL-CPG/60W/MK/120-347V/WH/D	60	120-347V	50,000	8100	30-40-50	≥ 80	Yes	10 x 3.1	1
3666316	Y	SSL-CPG/75W/MK/120-347V/WH/D	75	120-347V	50,000	10100	30-40-50	≥ 80	Yes	11 x 3.1	1
3666317	Y	SSL-CPG/100W/MK/120-347V/WH/D	100	120-347V	50,000	13500	30-40-50	≥ 80	Yes	11 x 3.1	1
3660154	-	SSL-CPG/LV/12V/SENSOR	SSL CPG canopy 12V DC microwave sensor								
3660155	-	SSL-CPG/LV/12V/CONTROLLER	SSL CPG Canopy 12V DC microwave sensor remote control								



SSL-CPG/LV/12V/SENSOR



SSL-CPG/LV/12V/CONTROLLER